




SYC 143



REDUCTOR DE PRESIÓN A PISTÓN PN 25

PN 25. Extremos Rosca Gas, H/H, ISO 228/1.
Temp. máxima 80°C. Asiento en acero inoxidable AISI 303. Regulación de 0,5 a 6 bares. Pretarado a 3 bares.

REDUTOR DE PRESSÃO DE PISTÃO PN25

PN25 Extremos rosca Gás, F/F, ISO 228/1.
Temp. máxima 80°C, Assento em aço inoxidável AISI 303. Regulável de 1,5 a 7 Bar. Pré regulado a 3Bar.

PISTON PRESSURE REDUCING VALVE PN 25

PN 25. Gas threaded, F/F, ISO 228/1. Maximum temp. 80° C. Stainless steel insert seat AISI 303. Outlet setting from 0.5 to 6 bars. Pre-set at the outlet pressure of 3 bars.

Medida Medida Size			Código Código Code	€	H	L
1/2"	1	25	RP143003		120	75
3/4"	1	20	RP143004		150	85
1"	1	15	RP143005		160	89
1 1/4"	1	6	RP143006		220	125
1 1/2"	1	6	RP143007		220	130
2"	1	4	RP143008		250	138
2 1/2"	1	4	RP14300A		260	145
3"	1	3	RP14300B		285	177
4"	1	2	RP14300C		310	190

www.france-arrosage.fr
infos@france-arrosage.fr

Tél. +33(0)4 42 22 60 05
Fax. +33(0)4 42 22 67 32

ZA Novactis - Quartier Jean de Bouc
CS 90032 - 13549 GARDANNE Cedex

S.A.S. au capital de 300 000 Euros - RCS Aix-en-Provence 81B310 - SIRET 322 407 271 00038 - APE 4661Z - TVA FR 02 322 407 271