



# FILTERS

## Filters & Pressure Reducers

### Barb and Thread Connections



Y-Filter / Pressure Reducer and Y-Filter  
3/4" Male Thread (Inlet & Outlet)



Y-Filter / Pressure Reducer & Y-Filter  
3/4" Female Thread (Inlet)  
x  
3/4" Male Thread (Outlet)

Easy to install Y-Filter / Pressure Reducer with 3/4" threaded connections  
In-Line Filters with thread and barb connections  
In-Line Pressure Reducer with 3/4" threaded connections

#### PRODUCT FEATURES

- Two Y-Filter with Pressure Reducers are available and Two Y-Filters without Pressure Reducers Y-Filter / Pressure Reducer & Y-Filter with 3/4" Male threaded connections (Inlet & Outlet) Y-Filter / Pressure Reducer & Y-Filter with 3/4" Female Thread (Inlet) and 3/4" Male Thread (Outlet).
- Nine In-Line Filters are available:  
Four In-Line Filters with 13 mm, 14 mm, 16 mm and 20 mm Barb connection (Inlet & Outlet).  
Four In-Line Filters with 3/4" Female Thread (Inlet) and 13 mm, 14 mm, 16 mm and 20 mm Barb (Outlet). One In-Line Filter with 3/4" Female Thread (Inlet) and 3/4" Male Thread (Outlet)
- The 150 Mesh Stainless Steel Filter Screen in the Y-Filter and the In-Line Filter traps particles in the water to reduce clogging of emitters.
- The Pressure Reducer controls mains water pressure at the outlet to 150 kPa (1.5 Bar)
- The 3/4" Female Threaded Nut on the Y-Filters, the In-Line Pressure Reducer and the In-Line Filters rotates independently from the body.

#### GENERAL APPLICATIONS

- Landscaped gardens, greenhouses and vegetable gardens



In-Line Filter  
13 mm Barb (Inlet & outlet)









In-Line Filter  
3/4" Female Thread (Inlet)  
x  
13 mm Barb (Outlet)



In-line Pressure Reducer  
3/4" Female Thread (Inlet)  
x  
3/4" Male Thread (Outlet)

#### FILTERS AND PRESSURE REDUCERS

PACKAGING															
		Y-Filter with Pressure Reducer	Y-Filter	Y-Filter with Pressure Reducer	Y-Filter	In-Line Pressure Reducer	In-line Filters Barbed (Inlet-Outlet)				In-line Filters 3/4" Female (Inlet) x Barb (Outlet)				In-line Filter Threaded (Inlet-Outlet)
							13 mm	14 mm	16 mm	20 mm	13 mm	14 mm	16 mm	20 mm	
Order Codes	PACKS	208218	208718	208228	208728	208233	208284	209404	208824	208834	208324	209414	208844	208854	209574
	BULK	020821	020871	020822	020872	020823	020828	020940	020882	020883	020832	020941	020884	020885	020957
Quantity per Bag	PACKS	1		1		20	25	25	25	25	25	25	25	25	25
	BULK	TBA		TBA		500	300	300	300	250	250	300	250	200	200
Bags per Carton	PACKS	TBA		TBA		25	12	12	12	10	10	12	10	8	8
	BULK	1		1		1	1	1	1	1	1	1	1	1	1
Weight per Carton (kg)	PACKS	TBA	TBA	TBA	TBA	15.5	9.2	9.5	9.5	9.2	9.2	9.4	9.3	7.7	9.4
	BULK	TBA	TBA	TBA	TBA	15.2	9.1	9.4	9.4	9.1	9.1	9.3	9.2	7.6	9.3
Inlet Connection		3/4" Male Thread		3/4" Female Thread		3/4" Female Thread	13 mm Barb	14 mm Barb	16 mm Barb	20 mm Barb	3/4" Female Thread				3/4" Male Thread
Outlet Connection				3/4" Male Thread		3/4" Male Thread					13 mm Barb	14 mm Barb	16 mm Barb	20 mm Barb	
Dimensions Assembled	HEIGHT	150 mm		154 mm		85 mm	133 mm				132 mm				118 mm
	WIDTH	110 mm		112 mm		33.5 mm									
	DEPTH	50 mm		50 mm		33.5 mm									
	WEIGHT	119.8 g	109.4 g	119.3 g	108.9 g	28.5 g	27.0 g	28.0 g	28.0 g	32.5 g	32.5 g	33.2 g	33.1 g	33.3 g	33.5 g
Material UV Stabilized		Polyamide		Polyamide		Polypropylene									